



Description

Skudo HT (Heavy Traffic) Commercial Mat can also be applied as a loose-laid protection system, alone or in combination with impact protection boards for commercial & residential projects. The HT Commercial Mat is a highly durable product for protecting concrete, while allowing the slab underneath to breathe, reducing the risk of hydration (cure) lines.

When used as a loose-laid system, simply lay the HT Commercial Mat out over the substrate, overlapping (50mm) where the edges of the matting meet, and tape along the seams to block debris, materials and spills from damaging the surface. If additional protection is needed, place the impact boards right on top of the HT Commercial Mat and tape to secure.

Skudo HT Commercial Mat, when applied as a loose-laid system, is designed to protect surfaces from damage for up to 12 months.

Uses

- Protects most surfaces, including freshly placed concrete as early as 14 days.
- Protects polished concrete and terrazzo*
- Areas can be polished and protected before interior walls are erected. Framing can be placed over the top of the Commercial System, which then can be left in place underneath
- Under Scaffolding & Shoring
- Flooring and Staircases

HT Commercial Mat can also be used on the following substrates:

Concrete*, Sheet Vinyl, Terrazzo*, Tile*, Stone*, Laminate, Epoxy, Hardwood, Carpet, Glass & Metal, Countertops, Joinery & more

**Speak with your Honcho Representative to confirm substrate suitability.*

Benefits

- Reliable surface protection for heavy foot traffic, trolleys and ladders
- Breathable system
- Superior spill, stain and water resistance
- Resistance to UV, rust, impact, and welding splatter
- Class 1 Fire/Flame retardant according to ASTM E 648 and NFPA 253 standards.
- Antibacterial/Antifungal: Test-verified protection against bacteria and moulds that cause infection. (ISO-20743)
- Safer working surface
- High slip resistance in wet and dry conditions
- Seamless and stationary



Protected in the United States by patent #10190004
Canada patent #2850385

Innovative, purpose-built surface protection systems. This is all we do.



Installation Steps

1. Ensure your surface is clean and dry before you lay Skudo HT Commercial Mat.
2. Kick the roll out in a straight line to create the first row.
3. When starting the second row, ensure to overlap the first row of matting, using the dotted lines as a guide.
4. Tape along the seams to secure the mat to itself, preventing dust, dirt and debris from getting in underneath.
5. Complete each row as above until your surface is covered.
6. For additional impact protection, we recommend placing Honcho Impact Boards over the top of the HT Commercial Mat.
7. We also recommend sufficiently securing/weighing down the mat/board around the perimeter of the protected area when used externally to minimise risk of displacement due to wind and extreme weather events



Innovative, purpose-built surface protection systems. This is all we do.